

KE 3 43A

RHEEM MANUFACTURING CO. RESEARCH & DEVELOPMENT DEPARTMENT

STANDARD TOLERANCE UNLESS OTHERWISE SPECIFIED  
-FRACTIONAL ±1/32  
-ANGULAR +3°-1°

REVISIONS

05 REVISED INSTR, DELC TED  
150, ALCO HOLE

F-1153  
12-3-87

06 CORRECT TIPO SAME WAS SOME JOP  
F-1158  
1-4-88

MATERIAL


DR. BY DATE JOE/11-23-87 ORIGINAL RELEASE NO.

NOTE: ALL BRAKES ARE 90° UNLESS OTHERWISE SPECIFIED

MILLEDGEVILLE GREENVILLE  
FLAT LAYOUT FT. SMITH

LABEL APPLICATION INSTR.

PART NO. ADS - 3978 REV. - 01 - 06

1. USE CLEAN CLOTH OR PAPER TO WIPE AREA CLEAN WHERE LABEL IS TO BE APPLIED.
  2. REMOVE LABEL FROM BACKING PAPER & CAREFULLY APPLY TO DESIGNATED AREA.  
  
CAUTION - DO NOT TOUCH ADHESIVE SURFACE AS ADHESION QUALITY MAY BE DESTROYED.
  3. OVERLAY LABEL (WHEN SPECIFIED) - REMOVE BACKING PAPER & APPLY SQUARLY OVER "UNDERLAY" LABEL SO SAME OVERLAP IS MAINTAINED ON ALL 4 EDGES OF UNDERLAY LABEL. 
- CAUTION - SAME CAUTION IN 2 ABOVE APPLIES.